

Technical datasheet Alloy 800H/HT / W-Nr.1.4876/1.4958/1.4959

A nickel-iron-chromium alloy with good creep rupture strength combined with excellent high temperature corrosion resistance used widely in chemical processing and heat treatment equipment.

Available products

Product form	Size range from	Size range to
Sheet/plate	0.5 mm thickness	15.0 mm thickness
Bar	8.0 mm diameter	160.0 mm diameter
Tube/pipe	17.1 mm outside diameter	219.1 mm outside diameter

Chemical composition (%)

	Ni	Fe	Cr	Al	Ti	Al+Ti	C
800H	30.0-35.0	39.5 min	19.0-23.0	0.15-0.60	0.15-0.60	0.30-1.20	0.05-0.10
800HT	30.0-35.0	39.5 min	19.0-23.0	0.25-0.60	0.25-0.60	0.85-1.20	0.06-0.10

Major specifications

ASTM B163, B407, B408, B409, B564, B829 DIN 17459, 17460	UNS N08810, N08811 BS 3072, 3074, 3076
---	---

Physical properties

Density	7.94 g/cm ³
Melting range	1357-1385°C

Mechanical properties – typical room temperature properties

Yield strength	170 MPa
Tensile strength	450-700 MPa
Elongation	35 %

Key attributes

Alloy 800H/HT has excellent resistance to oxidation and other forms of high temperature corrosion such as carburisation, sulphidation and nitridation thanks to the high content of Nickel and Chromium.

The high strength results from close control of the contents of Aluminium and Titanium combined with a high temperature annealing process to achieve a coarse grain structure (ASTM grain size 5 or coarser).

Alloy 800H/HT is highly fabricable and is readily formed by either hot or cold working processes. It is machinable and can be welded by conventional processes and procedures. Please contact us for further details on forming, fabrication and welding consumables.

Applications

Furnace equipment – furnace muffles, supports, baskets, burner components
Reformer tubes
Chemical process equipment – heat exchangers, vessels, steam generator tubing
Sheathing tubes

Do you require further information or a quotation?

Please contact us...

info@bibusmetals.com

www.bibusmetals.com

BIBUS METALS
SUPPORTING YOUR SUCCESS